

IN THE CLAIMS:

1. (currently amended) A method for operating a system that includes a plurality of valves, dampers, motors, and pumps, the system ~~that~~ is operable in a plurality of ~~normal~~ operating modes that each include interlocks between the modes, said method comprising:

operating the system in a first ~~normal~~-operating mode, the first ~~normal~~ operating mode comprising a predetermined configuration of valves, dampers, motors, and pumps; ~~and~~

selecting a second operating mode to switch the system operation to;

receiving a signal indicative of the system meeting permissive requirements for entering the selected mode;

initiating a predetermined time delay;

resetting each of the plurality of operating modes during the time delay; and

~~automatically~~ switching the system to a second ~~normal~~-operating mode without going to a standby mode, the second ~~normal~~-operating mode comprising a predetermined configuration of valves, dampers, motors, and pumps different than the first operating mode, and wherein at least one of the valves, dampers, motors, or pumps is positioned to a different operating position in the second operating mode than that respective valve, damper, motor, or pump was positioned for operation during the first ~~normal~~-operating mode.

2. (canceled)

3. (original) A method in accordance with Claim 1 wherein switching the system to a second mode comprises switching the system to a second mode without going to a standby mode, at least one of the first mode and the second mode comprises at least one of a residual heat removal mode, a reactor core isolation cooling mode, and a high pressure core flood mode.

4. (canceled)

5. (original) A method in accordance with Claim 1 further comprising verifying a plurality of second mode permissives prior to switching the system to the second mode.

6. (original) A method in accordance with Claim 1 wherein switching the system to a second mode without going to a standby mode comprises switching the system to a second mode using a fail safe initiation logic program.

7. (canceled)

8. (canceled)

9. (canceled)

10. (canceled)

11. (canceled)

12. (canceled)

13. (canceled)

14. (canceled)

15. (canceled)

16. (canceled)

17. (canceled)

18. (canceled)

19. (canceled)

20. (canceled)

21. (canceled)

22. (canceled)

23. (canceled)

24. (canceled)

25. (canceled)

26. (currently amended) A method for operating a nuclear power plant system that is operable in a plurality of ~~normal~~-operating modes that each include interlocks between the modes, said method comprising:

operating the system in a first ~~normal~~-operating mode, the first ~~normal~~ operating mode comprising a predetermined configuration of valves, dampers, motors, and pumps; and

selecting a second operating mode to switch the system operation to;

receiving a signal indicative of the system meeting permissive requirements for entering the selected mode;

initiating a predetermined time delay;

resetting each of the plurality of operating modes during the time delay; and

~~automatically~~ switching the system to a second ~~normal~~ operating mode without going to a standby mode, the second ~~normal~~ operating mode comprising a predetermined configuration of valves, dampers, motors, and pumps different than the first operating mode, and wherein at least one of the valves, dampers, motors, or pumps is positioned to a different operating position in the second operating mode than that respective valve, damper, motor, or pump was positioned for operation during the first ~~normal~~ operating mode.

27. (currently amended) A method in accordance with Claim 26 wherein ~~automatically~~ switching the system to a second mode comprises ~~automatically~~ switching the system to a second mode without going to a standby mode, at least one of the first mode and the second mode comprises at least one of a residual heat removal mode, a reactor core isolation cooling mode, and a high pressure core flood mode.

28. (previously presented) A method in accordance with Claim 26 further comprising manually changing at least one valve, damper, motor, or pump while operating in the first mode.

29. (previously presented) A method in accordance with Claim 26 further comprising verifying a plurality of second mode permissives prior to switching the system to the second mode.

30. (previously presented) A method in accordance with Claim 26 wherein switching the system to a second mode without going to a standby mode comprises switching the system to a second mode using a fail safe initiation logic program.